

Contents

| | M | |
|----|---|------|
| 1. | Manual:Extension/BlueSpiceBookshelf | 2 |
| 2. | Manual:Extension/BlueSpiceDiscovery | . 11 |
| 3. | Manual:Extension/BlueSpiceUniversalExport/Customization | 17 |
| 4. | Manual:Extension/ContentDroplets | 29 |
| 5. | Manual:Extension/ImportOfficeFiles | 41 |
| 6. | Manual:Preferences | 46 |
| 7. | Reference:BlueSpiceBookshelf | 63 |



Books

In BlueSpice pro, several wiki pages can be displayed for a structured book with chapter navigation. The book can also be printed as a PDF file with a cover sheet.

| Contents |
|--|
| 1 Characteristics of books |
| 2 Creating a book |
| 2.1 Adding pages4 |
| 2.2 Mass-adding of pages5 |
| 3 Adding metadata 5 |
| 3.1 Add graphic for gallery view |
| 4 Types of books 6 |
| 5 Exporting a book |
| 6 Actions in the book manager 6 |
| 7 Configuration |
| 7.1 Display options |
| 7.2 Export |
| 7.3 Configuring the file size limits (server) |
| 8 Deleting a book |
| 9 Duplicating a book |
| 10 Including a book table of contents on a page v4.4+ 11 |
| 11 Adding a PDF-download link to a page |
| 12 Permissions |




Characteristics of books

By default, books are created as a "general book". General books have the following characteristics:

- They povide a chapter navigation.
- $\bullet\hspace{0.4cm}$ On book pages, the book navigation is displayed instead of the main navigation.
- A wiki page that belongs to a general book is identified by a <bookshelf /> tag in the source code.
- Each page can only be included **in one** general book.
- Books can be printed completely or partially as a PDF with a cover sheet.
- They are listed alphabetically on the bookshelf. It is not possible to hide individual books.
- The bookshelf can be reached via the main navigation.

Creating a book


Books are created from the page *Special:BookshelfBookManager*. This page can be reached from the *Global actions* menu under *Management* > *Books*.



To create a book:

- 1. Click the + -button.
- 2. Enter a Book title.
- 3. **Select** "General books" as type of the book.






4. Click Done. The book editor loads next.


Important! The book is only created in the wiki when at least one page has been saved in the book.

Adding pages

You are now in the book editing mode.



- 1. Click the Plus button (1). A dialog window opens.
- 2. **Search** for a page in the wiki and select it. If a different name is to be displayed in the book navigation, you can enter a display title (optional).
- 3. Click Done.
- 4. **Add** additional pages.
- 1. **Click** the arrow of the *Save* button and select *Save and add chapter navigation*. This process inserts the <bookshelf /> tag into the source code of all wiki pages in the book. This causes a revision of the pages.





Tip: You can click a page title of a book page before adding a new book page. This is then inserted as a sub-chapter. You can move pages to the desired position later using drag & drop with the mouse.

The book is now displayed on the wiki bookshelf. The bookshelf can be reached via the entry links in the main navigation.

Note: There is no option to go directly from the bookshelf to the book manager.

Mass-adding of pages

After clicking "Mass add", a dialog is opened. It contains different criteria for page selection:

- All pages of a category
- All subpages of a certain page
- From a page collection page collections are lists of pages located in the MediaWiki namespace. They are usually created from a Word import or from search results.

After adding your book pages click Save at the bottom of the page. Now you have created a page in the namespace Book. It simply contains the list of pages that have been added to the book.

Adding metadata

While editing a book (adding or removing pages), metadata for the book can be added. References to these metadata can be included in the PDF template. To edit metadata, select the top-most node of the book (first page) and click the wrench icon. A dialog with a drop-down selection of the following options is available:

- Title
- Subtitle
- Author 1
- Author 2
- Document-ID
- Document type
- Department
- Version
- Bookshelf image
- Template (PDF): If you maintain multiple PDF templates for books, you can select one of them here.
- Table of Contents (*Only article titles*, or *Embed article TOCs*)

It is also possible to add your own met data for use in the <booklist>-tag, for example.



Add graphic for gallery view

Add the *Bookshelf image* metadata element to add a cover photo for a book in the bookshelf gallery view. Select this option from the drop-down list and click *Add*. Then enter the name of the image (without the "File:" prefix) in the value field. Any image currently uploaded to the wiki can be used. The image will then be displayed in the book gallery. However, the image is not used as a cover image for the PDF export (exception: *BlueSpice cloud*).

Types of books

| Туре | Description | Chapter navigation |
|--------------------|--|-----------------------|
| General books | Visible to all users. Only general books can have a chapter navigation. In almost all cases a book is set up as a "general book". | Yes |
| Own books | An own book is only visible in the bookshelf to the user who created the book. Such a book does not have a chapter navigation. Own books are usually created to export wiki pages as a PDF with a cover sheet. | No |
| Temporary books | This selection is also available to wiki users who are not logged into the wiki and is therefore mainly useful for public wikis. These books are only temporarily stored in the user's browser and not in the wiki itself. If the browser cache is deleted or the user switches to another browser, the book is no longer available. The main aim of temporary books is so that users can collectively print out wiki pages as PDFs. | |

Exporting a book

Books, individual chapters or even individual book pages can be exported as PDF files:

- 1. **Open** the book in the book manager.
- 2. **Select** each of the pages or chapters to export by clicking the appropriate check boxes. Sub-chapters are selected automatically.
- 3. Click the Export Selections drop-down menu to open a list of the available formats.

Actions in the book manager

The link Administration > Books in the menu *Global Actions* loads the page *Special:Book Administration*. Here you can edit your books.






- Edit (1): Links to the Book editor where you can edit the book contents and metadata.
- Delete (2): Deletes the book page in the namespace Book without deleting the wiki pages.
- **Duplicate** (3): Duplicates this book, including **all the pages** of the book to a different namespace.
- Export (4): Exports all wiki pages in this book to PDF.
- Assign (5): Assigns the book to designated users. These users are the responsible editors of the book.

Configuration


Display options

- Show book chapter pager after content: Displays previous/next book page navigation at the end of each book page. (1)
- Show book chapter pager before content: Displays previous/next book page navigation at the beginning of each book page. (2)






• Use the display title from book source on article: Shows the title from the book navigation as page title instead of the page name.



Note: If the page additionally contains a {{DISPLAYTITLE}} tag, the display title of the page is shown instead of the book title.



Prepend article table of contents and headlines with book numberation: The page TOC does
not start with the main heading 1, but with the actual number from the book chapter (see screenshot). If
users have activated in their user preferences to "auto-number headings", the numbering system is
matched accordingly.



 Supress namespace prefix of book articles in output: The namespace prefix of an article is not shown in PDFs.

Export

Wiki administrators can make the following adjustments for the book export:

Configuring the file size limits (server)

By default, the book export is limited to 50MB in file size. To adjust this value, complete the following steps:

1. In Apache Tomcat, open the file web.xml:

```
sudo -s
nano /opt/tomcat/webapps/manager/WEB-INF/web.xml
```

2. Look for the following lines and adjust the value (e.g. for 250MB=26214400)

```
<max-file-size>262144000</max-file-size>
<max-request-size>262144000</max-request-size>
```

3. The web app BShtml2PDF also has a setting that needs to be adjusted:

```
nano /opt/tomcat/webapps/BShtml2PDF/WEB-INF
```



4. Enter your values in the following lines:

```
<param-name>maxMemSize</param-name> <param-value>26214400</param-value>
<param-name>maxFileize</param-name> <param-value>26214400</param-value>
```

5. Restart Apache Tomcat

```
service tomcat restart
```

Deleting a book

When you delete a book, you only remove the book page of the book (that is, the table of contents) in the "Book" namespace. However, the wiki pages in the book are not deleted. Before deleting the book, a pop-up menu informs you that the *bookshelf-tag* will not be automatically removed from the pages.

The *bookshelf* tags have no effect on the wiki pages after deleting the book page. If you want to remove them manually, you can go to the page *Special:ReplaceText* and do a "find and replace".

Duplicating a book

You can create an entire copy of the book by duplicating it:

To duplicate a book:

- 1. **Enter** a *target name*: The default value is the book name with the suffix *(copy)*. Change this to create a different book title.
- 2. **Select** a *namespace*: Choose a namespace that is different from the original namespace.

If you are not careful, you might experience some unintended consequences. By creating a new book, you also create copies of all the wiki pages in the original book. Since a namespace cannot contain the same page twice, you have to copy the files to a different namespace.

About the duplicated files:

- **Book page:** A new page in the namespace book. If you don't enter a new title, the book will be created with the same title and the suffix (Copy). E.g. Employee Manual (Copy). This file includes a copy of the structure of your original book with the corresponding links to the duplicated pages in the new copy.
- **Wiki pages**: All pages contained in the original book are duplicated. The following scenarios are possible:
 - **Same namespace:** If you duplicate a book in the same namespace, no actual duplicates of the actual wiki are created. Instead, the bookshelf tag is updated to point to the copy of the book. For example, if your original book contains the page *HR:Quality assurance* (the book is in the namespace HR), the *Quality assurance* page now contains the bookshelf tag
 - Olfferent namespace: If you create the book copy in a different namespace, the bookshelf tag in the original files remains unchanged. The new pages in the different namespace are created with a bookshelf tag for the new book copy. This is most likely the scenario you want.



Including a book table of contents on a page v4.4+

The Content droplet "Book table of contents" can be used to insert the an entire book TOC or an individual chapter navigation of a book on any wiki page.



Adding a PDF-download link to a page

The Content droplet "Book PDF link" can be used to insert a link on a page that will download a book directly as a PDF.

Permissions

To create and edit books, users need *edit* rights in Book namespace. Additionally, a user can only add pages to the book that that user can read. If a user tries to export a book to PDF that contains pages for which the user does not have permissions, the user will get an error message.



Layout


Books

| 5 Work area | . 16 |
|---------------------------|------|
| 5.1 Breadcrumb navigation | . 16 |
| 6 Page appendix | . 16 |
| 7 Footer | . 17 |



BlueSpice Layout

The user interface is divided into distinct areas that group various wiki functions in a meaningful way. Here you get an overview of all features of the standard skin "Discovery".



| Bereich | Beschreibung |
|-------------------|--|
| 1-Header bar | Contains important elements such as the logo area, the search field and the buttons for various navigation menus (mega menus). |
| 2-Main navigation | The "heart" of the site organization. The navigation links can be customized by admin users. This area also displays the book navigation. |
| 3-Page tools | Contains all the actions that can be performed on a page. In addition, information such as the version history or the page information can be accessed from here. |
| 4-Work area | All content is created and edited here. The work area is divided into the title area and the actual page content. |
| 5-Page appendix | Additional information such as category membership, discussions and attachments are displayed in the supplementary area. In addition, page recommendations and ratings are displayed if they are activated for the page. |
| | The footer contains links to legal information as well as to external |



| Bereich | Beschreibung |
|----------|---------------------------------|
| 6-Footer | websites relating to MediaWiki. |

Header bar

The header contains important elements such as the logo area, the search field and the buttons for various navigation menus (mega menus).



| Funktion | Beschreibung |
|---------------------------|--|
| 1a-Main navigation toggle | Allows users to show and hide the main navigation. |
| 1b-Logo | The logo can be changed using the special page FlexiSkin. |
| 1c-Search field | Page titles that match the search expression are displayed in a quick menu while the search term is being entered. Pressing the Enter key takes you to the search center, which displays the results of a full-text search and allows filtering the results. |
| 1d-"New content" button | The "New" button allows to create a new page. A subpage can be created directly via the submenu or a new file can be uploaded. A multi-upload is only possible via theManual:Extension/ExtendedFileList. |
| 1e-Custom menu | Allows users with admin rights to create an additional mega menu. The button is only displayed once the additional menu has been created. |
| 1f-Global actions | Direct links to many special pages as well as administrative pages of the wiki. |
| 1g-Language selection | If a page includes links to pages in different versions via language codes that were defined in the Interwikilinks, a mega menu is shown for the language selection. |
| 1h-User menu | Users manage their own settings, tasks and notifications here. A red circle appears above the user avatar if unread notifications exist. |
| 1i-Page tools toggle | Allows users to show and hide the page tools of a page. |


Main navigation



Links to the most important wiki pages are shown here. Administrators have the option to customize the main navigation.

Page tools

The page tools area contains all the actions that can be performed on a page. In addition, information such as the version history or the page information can be called up from here.



| Funktion | Beschreibung |
|---------------------|---|
| 3a-Standard actions | Move, Copy, Delete, Refresh |
| 3b-Extended actions | Start a workflow, Set expiry, Set reminder, Set page assignments, Add to book |
| 3c-Quick actions | Export options, Share, Add to watchlist |
| 3d-Page details | Page history, Page information, Browse properties |




| Funktion | Beschreibung |
|----------------|---|
| 3e-All actions | Opens a dialog window, in which all possible actions on this page are listed. |

Work area

Breadcrumb navigation

The breadcrumb navigation at the beginning of the work area consists of links that map the path of the current page:

Namespace (=root node) > Pagename > Subpage level 1 > ... > Subpage level x



If the page <namespace>:Main_Page (languae variations: de:Hauptseite | fr:Accueil | zh:) exists, the root node links to that page.

If this page does not exist, the root node links to "All pages" (*Special:Allpages*) with the namespace selector preset to the respective namespace. If the root node should link to a different page (e.g., <namespace>:Portal), then this page needs to be redirected to the page <namespace>:Main_Page.

Page appendix

To hide the page appendix area, the following CSS rules can be added to the page *MediaWiki: Common.css*:

Hide entire area:

```
#data-after-content {display:none} /* Hide discussions and attachments */
```

Hide attachment only (only up to BlueSpice v4.1):

```
#social-stash-cnt {display:none} /* hide only attachements */
```



Hide discussions only:

```
#social-topics-cnt {display:none} /* hide only discussions */
```

The areas above can also be hidden by namespace, e.g.:

.ns-0 #data-after-content, .ns-3000 #data-after-content {display:none} /*Hide only in some namespaces*/

Footer

The footer contains links to legal information as well as to external websites relating to MediaWiki. The links to the legal information can be adjusted by wiki administrators via pages in the MediaWiki namespace.

Customize the footer



Technical Reference: BlueSpiceDiscovery

PDF Customization (Cloud only)

The standard PDF template in BlueSpice Cloud can be adjusted directly in the wiki.

Important! In non-cloud editions, the PDF template has to be adjusted on the server.

Contents

| 1 Header and footer | |
|--|----|
| 1.1 Available parameters | |
| 1.2.1 Using custom text | |
| 1.2.2 Removing the middle column | |
| 1.2.3 Adding a margin before and after the header | |
| 1.3 Footer | |
| 1.4 Header and footer background color | |
| 2 Book cover | |
| 2.1 Using a cover image | |
| 2.1.1 Defining the background image and the subtitle | |
| 2.1.2 Using background colors | 26 |

Books


| 3 Tags | 28 |
|------------------------|----|
| 3.1 Landscape printing | 28 |
| 4 Related info | 29 |



Header and footer

| Ву | By default, the PDF template contains 3 sections | for the header and 3 sections for the footer. |
|----|--|---|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |





Both the content and the number of columns in the header and footer area can be edited in the following files.

5

6

MediaWiki:UniversalExport/PDF/Default/Header.html

4

Standard PDF template



- MediaWiki:UniversalExport/PDF/Default/Footer.html
- MediaWiki: UniversalExport/PDF/Default/Styles.less (optionales externes Stylesheet)

Available parameters

The following content can be added to each section in the header or footer:

| Parameter | Description | |
|-------------------|---|--|
| logo | current wiki logo | |
| title | title of the page. In books, this is the title of the book page. | |
| subtitle | prints the subtitle of a book if a subtitle was created in the book meta data | |
| currentpagenumber | number of the current page | |
| totalpagescount | total number of pages | |
| url | URL of the wiki page | |
| user | username of user who printed the page | |
| exportdate | date of PDF-creation | |
| exporttime | time of PDF-creation | |

Each parameter is added to the header or footer enclosed in three curly brackets, for example: {{{logo}}}.

In addition, you can simply type in regular text in each section.

Header

The header contains a wiki table with three columns. The default content for the first column is the logo of the wiki and the last column shows the page title. The middle column is empty.

To make changes to the header, open the page *MediaWiki:UniversalExport/PDF/Default/Header. html* in edit mode.





Using custom text

If you do not want to show the logo, but display custom text, you can simply delete the existing placeholders and replace them with your text. Be aware that this header will be used for all PDFs on your wiki, including books.

Any of the columns can be left blank.

```
{|
| Text in left column || Text in middle column || Text in right column
|}
```

Removing the middle column

By default, the 3 columns each use 1/3 of the header width. If you need more room for the left or right column, you can remove the middle column. The remaining 2 columns than each get 1/2 of the header width.

```
\{\mid |The left column now uses 50% of the header width. \mid\mid Text in the right column \mid\}
```

The left column now uses 50% of the header width.

Text in right column

Product info

What is BlueSpice?

With BlueSpice MediaWiki you enable your employees to quickly access current and business-critical knowledge via a central and dynamic knowledge base. BlueSpice is an open-source enterprise software that offers you many advantages: It is stable, secure, and relies on state-of-the-art web technologies. You retain control over the source code and ensure that all developments remain publicly available. In keeping with the open-source philosophy, there is also a free distribution in addition to the paid editions pro and farm.



Adding a margin before and after the header

The margin before and after the header can be adjusted by changing the beginning of the table to include a style declaration:

Footer

The footer can be customized just like the header.

By default, the footer shows the creation date of the pdf, a BlueSpice disclaimer, and the page number with number of total pages.

```
{|
| {{{exportdate}}} || {{int:universal-export-pdf-default-disclaimer}} ||
{{{currentpagenumber}}} / {{{totalpagescount}}}
|}
```

To make changes to the footer, open the page *MediaWiki:UniversalExport/PDF/Default/Footer.html* in edit mode. For example, you could replace the BlueSpice disclaimer in the middle column with the username of the user who printed the pdf.

```
{|
| {{{exportdate}}} || {{{user}}} || {{{currentpagenumber}}} / {{{totalpagescount}}}
|}
```

BlueSpice pro on your own server (On Premises)

Most of our customers run their BlueSpice on their own servers (Windows or Linux) in-house, thus ensuring optimum integration into their IT infrastructure. If the server has very high loads, then you can scale up the operation to several servers. Connections to user directories and central backup systems, operation behind firewalls and proxies, and integration with intranet portals are possible.

External content from Office products can be migrated to BlueSpice pro. Alterations to the software and the integration of additional MediaWiki extensions on your own server are no problem. We would be happy to help you with the installation and setup of BlueSpice pro.

07.01.2021 WikiSysop 1 / 1

PDF footer showing username



Header and footer background color


If you want to use a background-color for the header and footer, you can copy the following style declaration at the end of the page *MediaWiki: UniversalExport/PDF/Default/Styles.less*:

```
#runningheaderfix, #runningfooterfix {
background-color: #eee;
}
#runningheaderfix > table {
border-bottom: none !important;
}
#runningfooterfix > table {
border-top: none !important;
}
```

Book cover

When you print a book to PDF, the book has a basic cover page.

By default, the cover page contains the logo, book title, and a placeholder for the subtitle. If you did not create a subtitle for your book, no subtitle is shown.





Using a cover image

To customize the cover page for books, you will edit the page *MediaWiki:UniversalExport/PDF /Default/Cover page.html* .

The example shown below contains the following elements:

- Logo
- Background image
- Title
- Subtitle



This cover page was created with the following source code. You can simply overwrite the existing content:

```
{{{coverbackground}}}
{| style="width: 100%; text-align: right;"
|{{{logo}}}
|}
<div style="font-size: 18pt; font-weight:bold; margin-top:5cm; color:#333333">
{{{title}}}</div>
<div style="font-size: 14pt; margin-top:11.5cm; color:#333333">{{{subtitle}}}</div>
```


- Lines 1-3: A table with the wiki logo.
- Line 4: Title here you can define, for example, the font size and font weight, the margin to the top of the page and the font color.
- Line 5: Subtitle same as the title. The property *margin-top* sets the distance between title and subtitle.



Defining the background image and the subtitle

The subtitle and background image are set in the book's metadata.

- 1. Go to the book manager.
- 2. Select the book for which you want to customize the cover page. This should be an image with the **full page dimensions** (e.g., DIN A4 or letter size) since it will be shown as a background image.
- 3. On the book editing page, click the wrench. This opens the metadata dialog.



- 4. Type *coverbackground* in the drop-down menu (1) and click *Add* (2). In the right column, enter the name of the picture that you want to use for the background. The picture must be uploaded to the wiki. If your picture has a namespace prefix, this must be included in the image name.
- 5. Select *Subtitle* from the drop-down menu (1) and click Add (2). Entehe desired subtitle accordingly in the right column.
- 6. Click Done.
- 7. Finally, click *Save* at the end of the book editing page.

Now test the layout by printing the book as a PDF using the book management. To make the necessary changes (e.g., spacing between title and subtitle), change the settings accordingly on the <code>MediaWiki:UniversalExport/PDF/Default/Cover page.html</code> or in the metadata.


Note: You can define a separate background image for each book using the book's the metadata. However, the picture should always be placed in the same position, since all books share the *Cover page.html*. The alignment of the text elements is shared between all cover pages.


Using background colors

If you do not have a background image for your book covers or if you don't want to use one, you can also work with colors to customize the cover page.




Here are some examples and the needed source text for the page *MediaWiki:UniversalExport/PDF /Default/Cover page.html*. To use them, simply overwrite the existing content in that page.





Cover page 1



Cover page 2

Cover page 1

```
<!-- Logo -->
{| style="width: 100%; text-align: right;"
|{{{logo}}}}
```



Cover page 2

Cover page 3

```
<!-- Logo -->
{| style="width: 100%; text-align: right;"
|{{{logo}}}
|}

<!-- Title block with background color -->
<div style="background-color:#c6752d; margin:4.5cm -2cm 0 -2cm; padding:2cm 2cm 3cm 2cm;">
<div style="font-size: 24pt; font-weight:bold; margin-bottom:0.5cm; color:#ffffff;">
{{title}}
</div>
<!-- Subtitle block -->
<div style="font-size: 18pt; margin-top:0.5cm; color:#efefef">{{subtitle}}}
</div>
</div></div></div></div></div>
```

Tags

Landscape printing

To print a PDF page in landscape format, the following tag can be inserted in the wiki page in source editing mode at any position:

```
<bs:ueparams template="BlueSpiceCloudLandscape" />
```



To make it easier for the user to add this tag with the visual editor, this tag can be added to a wikitext-template, for example, [{LandscapeFormatExport}}]. The element can be inserted anywhere on the page.

Note: This tag only works for the PDF single page export.

Related info

Cloud administration

Content Droplets

*

ContentDroplets is available from BlueSpice 4.3.2.

Contents

| 1 | Adding a droplet to a page | 30 |
|---|----------------------------|----|
| 2 | List of droplets | 30 |
| 2 | More info | 40 |




To insert additional functionality in a wiki page, you can use Content droplets. Content droplets include tags that were previously accessed from *Insert > Magic word* in the editor toolbar. They also provide access to some templates that are preconfigured in the wiki, such as message boxes.

Adding a droplet to a page

To add a droplet to a page:

- 1. **Click** the Content droplets icon in the editor toolbar or type << .
- 2. **Search** for a droplet name in the search bar of the droplets menu or browse the droplets by category.



- 3. Select a droplet
- 4. Click Insert.


Note: Some droplets open an inspector menu which contains another *Insert* button. Be sure to confirm that button as well.

Based on the type of droplet, you can continue with configuring the droplet as needed.


List of droplets

→ View examples of droplets outputs.












| | Droplet | | Descrip | |
|--------------------------|---|-------------------------|---|--|
| ode | :kground:blue;} r a css example | | Highlight section for code example | |
| eate page | | | Form field predefine page crea | |
| ata query | | | Enables queries of content in the wiki | |
| te v4.4+ | | 2023-11-23 Date display | Inserts a This can used in combinat with the content droplet To | |
| ecision | Eat more veggies | | Highlight decision | |
| | Decision output | | page property | |
| cision overview | | | | |
| Page | Decisions | | | |
| Product feature requests | Extension TabberNeue will be added to version 4.4 | | Table with | |
| CollabPad QATesting | Ownership: Team Prod | | list of decisions were crea by the <i>Dec</i> content dr | |
| Minutes:IT/2023-11-20 | Release cycles are extended from 30 to 40 days | | | |
| | | | | |







| Drople | t | Descript |
|---|--|--|
| Heading Message text Message of type "important" | | panel for important note |
| Links to this page | | List of pacthat link this page |
| List of users logged in | | Pop-up w list of all users tha are curre logged in |
| Karisplatz (Stachus) Hackenvie Klinikviertel Anger Ludwigsvorstadt | viertel Isartor Haidh Gartnerplatz Haidhausen-Süd | Locations be marke the map |
| Mathematical formula | $egin{array}{lll} z &=& a \ f(x,y,z) &=& x+y+z \ \end{array}$ Screenshot of a math formula | Display o mathema formulas |
| Member list | | List of members wiki group |




| | Droplet | Descrip |
|-----------------------|---------------------------------------|--|
| Message A plain | Heading Message text message | Adds tex panel |
| Modal button | | Configur button w opens a customiz modal dialogue |
| Most visited pages | | List of th most vis wiki page |
| New users | | List of ne users in wiki |
| Note Message Message | Heading Message text e of type "Note" | Adds col panel for note |
| Number of characters | | Shows the number characte words in wiki pag |
| Number of files | | Shows th number uploaded files |
| Number of pages | | Shows th number pages |
| | | Shows th |




| | Droplet | Descript |
|--------------------|--|---|
| Number of users | | number o |
| Number of users lo | ogged in | Number o currently logged in users |
| Page access | Access to this page is restricted to the group sysop. Page access notification banner | Restricts access to page to the specified groups |
| PDF link | | Link that download another w page as P |
| PDF page break | | Forces a page brea the set position during PD export |
| PDF preview | | Embed preview of PDF file |
| PDF no export | | Content within this section is excluded from the F |
| Progress | | Visualizes progress against gi measuren variables |
| Pros and cons | | |












| | Droplet | Descript |
|-----------------|---|---|
| Video | | external platforms (YouTube) |
| Visited pages | | List with visited pa |
| Warning Message | Heading Message text Message of type "warning" | Adds a colored bo for a warr note |
| Watchlist | | Latest changes t pages included i your wate |

More info

- Adding your own droplets
- Checklist
- Examples
- Icon
- Progress



Technical Reference: ContentDroplets



Word Import



The Word import is is available from BlueSpice 4.2.

Contents

| 1 What is the Word import? | 42 |
|--|----|
| 2 Import a word document | 42 |
| 3 Create a book | 43 |
| 3.1 Change the display title of your book chapters | 45 |
| 4 Sources of error | 46 |
| 4.1 Images are not imported | 46 |
| 5 Related info | 46 |



What is the Word import?


The extension **ImportOfficeFiles** allows importing a Word document which will be converted to wiki pages.

- The file can be converted to a single page or to a page with subpages.
- Image files are also imported.
- Imported pages can be used as a page collection for creating a book.


Import a word document

To import a Word document:

1. Click New > Import Word file in the top menu.




2. **Click** *Select a file* or drag the Word file in the drop zone.



- 3. Click Next.
- 4. Choose the import settings you want.





- 1. **Title:**The title of the wiki page generated by the import. When the content structure is broken up, the chapters are created as sub-pages of this main page.
- 2. **Content structure:** If the "Split content to pages" checkbox is activated, subpages are created from the heading levels of the Word document. This is possible up to 3 levels deep.
- 3. Conflicts with page title:
 - Rename: The imported page is created as <page name> (1). However, this should be avoided, especially with large Word files that are divided into additional levels. It is best to enter a new page title here as an alternative. A naming conflict is displayed in the preview. In this case, if necessary, click Cancel to start the import with a new title. Or select "Override" as a conflict resolution.
 - Override: The existing page(s) will be overwritten with a new version.
- 5. Click Next.

The preview shows: (1) the names of the pages that will be created (2) via the arrow icon: the files that will be imported for the individual pages (3) via the eye icon: the content of the individual wiki pages.

6. **Click** *Import*. After the import is complete, the created pages are displayed as a page collection in the wiki. You can view the pages from this page by clicking on the link.


Note: In a wiki installed with "German" as the content language (contentlanguage), the path to the page starts with *MediaWiki:Page collection*.

Create a book


It is easy to create a book from the imported pages:

- 1. Click the plus button.
- 2. Enter a book title and click Done.
- 3. Click the Bulk Add button.
- 4. **Select** Page Collection as the source.
- 5. **Select t**he page name of the imported file.






The pages have been added.



- 6. Choose Save and add book navigation to each wiki page from the Save menu.
- 7. **Click** *OK* in the dialog "Change wikipage" associations. This will add the chapter navigation to each book in the page.






add bookshelf tag to book pages

The book is now available on the Bookshelf page of your wiki.

Change the display title of your book chapters

Since the display titles of the book pages show the path of the imported subpages, it makes sense to edit the display titles afterwards. To do this, open the book page in source edit mode and remove the path with the trailing "/".




If the book has a lot of pages, you can copy the source code into an editor like Notepad++ and replace the following text:

|Employee handbook/

Replace the text and take care that the vertical pipe after the actual page name and before the page title is the replacement text.

Copy the source code back to the wiki and save the book page.





Sources of error

Images are not imported

- Images have a background/shadow and only the background/shadow is imported: These images are not supported. Solution: Remove the background/shadow before the import.
- Images are embedded as .tmp files in the Word document for an unknown reason. Solution: Before importing, save the images from the Word document locally and then use them to replace the original image in the Word document.

Related info

- Reference:ImportOfficeFiles
- Books





Personalization

| Contents | |
|---------------------------------|----|
| 1 Accessing preference settings | 49 |
| 2 User profile | 49 |
| 2.1 Basic Information | 49 |
| 2.2 Internationalisation | 49 |
| 2.3 Signature | 49 |
| 2.4 Email options | 49 |
| 2.5 WebDAV | 50 |
| 3 Appearance | 50 |
| 3.1 Skin | 50 |
| 3.2 Reading preferences | 50 |
| 3.3 Date format | 50 |
| 3.4 Time offset | 50 |
| 3.5 Files | 50 |
| 3.6 Diffs | 52 |
| 3.7 Advanced options | 52 |
| 3.8 Bookshelf special page | 53 |
| 3.9 Context menu | 53 |
| 3.10 Dashboards | 54 |
| 3.11 Video player | 54 |
| 3.12 Timeline | 54 |
| 4 Editing | 54 |
| 4.1 General options | 54 |
| 4.2 Editor | 55 |
| 4.3 Preview | 56 |
| 4.4 Reminder | 57 |
| 4.5 Timeline | 57 |
| 5 Recent changes | 57 |
| 5.1 Display options | 57 |
| 5.2 Advanced options | 58 |
| 5.3 Changes shown | 58 |
| 5.4 Edit review | 58 |
| 6 Watchlist | 59 |
| 6.1 Edit watchlist | 59 |
| 6.2 Display options | 59 |
| 6.3 Advanced options | 59 |
| 6.4 Changes shown | 60 |
| 6.5 Watched pages | 60 |
| 6.6 Token | 61 |
| 7 Notifications | |
| 7.1 Email options | 61 |

| 7.2 Notify me about these events | 62 |
|---------------------------------------|----|
| 7.3 New message indicator | 62 |
| 7.4 Notifications on namespace events | 62 |
| 7.5 Notifications on categories | 62 |
| 7.6 Review | 62 |
| 8 Extended Search | 62 |
| 9 Semantic MediaWiki | 62 |
| 10 Resetting all preferences | 63 |




Accessing preference settings

- 1. Click on the user menu.
- 2. **Click** *Preferences*. This opens the preferences page with multiple tabs.

Alternatively, you can access the page Special:Preferences directly.

User profile

Basic Information



- **Real name**: This name is shown throughout the wiki. When users hover over your real name, your profile picture and contact information is shown.
- **Change password**: If your wiki is not connected with the central authentication system of your company, you can manage your password here.
- User image:
 - User image text field: Enter the webadress of a picture on another website and click Save at the bottom of the page. The profile picture points directly to the external image:
 - Change profile picture link: Upload an image to the wiki. Click Browse and then Upload to create a new profile image. If you click Generate new avatar, the system generates a graphic instead.
- Privacy policy acceptance checkbox: Select and save this checkbox setting to confirm that your accept
 the privacy policy. Administrators can review this setting for all users on the page Special:Privacy_Admin.

Internationalisation

- Language: Users can change their personal language that is used in the layout and menus. BlueSpice currently supports de-formal-German (formal), de-German and en-English.
- How do you prefer to be described? Option for setting your gender preferences.

Signature

- Your existing signature: shows a preview of your current signature including your profile info when you hover over the link.
- New signature: Enter a new name for your signature and save the Preferences page.
- Treat signature as wikitext: Your signature will be shown as text-only.

Email options

If you provide an email address, you can specify to receive email notifications in addition or in place of wiki notifications. As long as the email address is not confirmed, the system will not send emails. This also affects the settings in the Notifications tab.



WebDAV

This link is used as mounting path to your wiki. It only works if your server administrator has configured a WebDAV connection. By default, no WebDAV connection is configured.

Appearance

Skin

If your system has more than one skin installed, you can select one here. It only affects your view. All other users see the skin that is selected in their preferences.

Reading preferences

Page previews: You can set if you want to see the first lines of an article as a tool tip before you click on a link. This functionality is provided by the extension Popups.

Date format

You can set how you would like to see the timestamp on wiki pages, for example the timestamp of a user signature on a discussion page.

Rodrigue (talk) 09:10, 3 December 2019 (CET)

Time offset

- **Server time:** Shows the server time so that you can compare it to your local time.
- **Local time:** Shows the time set in the time zone setting.
- **Time zone:** When you select a time zone, your local time will be shown throughout the wiki wherever there is a timestamp.


Files

• Image size limit: Sets the maximum size of the preview image on the file description page.





- **Thumbnail size:** Sets the size of the thumbnail image on a page if no custom size is specified in the image settings.
- **Enable Media Viewer:** If this checkbox is not selected, image links on a page will load the file description page rather than the media viewer overlay.





Diffs


Diffs are a comparison view between different versions of a page. They are accessible from the version history of a page. You can select two versions for a comparison and then click *Compare selected revisions* to view the differences.

- **Do not show the page content below diffs:** Turns off the display of the current page preview below the differences view.
- **Don't show diff after performing a rollback:** After an administrator does a rollback of a page, the difference between the previous latest and the current latest version is shown by default. If turned off, the rollback loads the current page directly instead.
- **Don't show the revision slider:** By default there is a collapsed interactive graph of the revision history. This graph can be deactivated.

Advanced options

Link underlining:

Always: Underlines all links in the content area of a page, even if the selected skin specifies no underlining. The table of contents is not affected by this setting.



- Never: Never underlines links in the content area of a page, even if the selected skin specifies underlining.
- O Skin or browser default: Keeps the link settings as specified in the skin.
- Threshold for stub link formatting: Determines when the target page is considered short enough to change the link color to a page that fits the threshhold criteria. If you choose 50 bytes, a link to a page with less than 50 characters (including wikitext), will be marked as a stub link and be shown in a different color. This only works if your wiki skin has a separate color value for stub links defined.
- Auto-number headings -v4.3: Adds heading numbers to the page headings. Note: The heading numbers for books are set independently by administrators in the Config manager.




5 Handling and storage If caustic soda is left unsealed in the air, it will react with carbon dioxid hermetically sealed containers. 5.1 Safe handling advice Use and open container with care. Avoid dust formation. Supply eye wash bottle. 5.2 Advice on protection against fire and explosion No special actions required.

• Show a confirmation prompt when clicking on a rollback link: If an admin user wants to perform a rollback of multiple options from the version history of a page, the rollback is executed immediately after clickint the link by default. With this setting, the admin user needs to click on the "Rollback" link again to confirm the rollback before it is executed.

Bookshelf special page

Grid: Shows the details view (=list view) of available books by default (2)


Images: Shows the thumbnails view of available books by default (1)



Context menu

Page links in the content area of the wiki show a context menu that allows to perform actions on the target page without having to go to the target page first. You can set whether you want to show the context menu with *right-click* or with *right-click* + *Strg*.





Dashboards

By default, the logo of your wiki links to the main page. You can change this and link to your user dashboard instead.


Video player

When a page contains a video that was inserted with the BlueSpicePlayer extension, you can set it to autoplay when you load a page.

Timeline

You can set the timestamp on the timeline entries in date format or as age.

Note: It can take up to 24 hours for all timeline entries to show the new timestamp format. When you create a new entry, you shouls see the changed format immediately.




Editing

General options

• Enable section editing by right clicking on section titles: Right-clicking a section title with the mouse sets the page in edit mode. The specified section can be edited immediately.



- Editing pages by double clicking (JavaScript): Double-clicking on the page sets the page in edit mode. The double-click needs to be inside the text area of the page. Clicking in the title section of a page will not set the page into edit mode.
- Enable the Paragraph-based Edit Conflict Interface to resolve edit conflicts: Allows section-based merging of differences which improves the process for solving edit conflicts between users. If this setting is disabled: Users will see the source code of the latest version, a diff view between the latest and the own version, and a source diting window to manually work on the user's unsaved version.
- Show the pending changes diff when editing pages: In the BlueSpice 4 Discovery skin, no visual diff is shown during editing, so this setting can be ignored. It simply adds a duplicate notice about pending changes, when opening a page in edit mode:




Editor

• Edit area font style: Displays source code in monospace, serif, or sans-serif font.

Note: This setting is ignored if the CodeMirror extension is enabled (from BlueSpice 4.2).

 Mark all edits minor by default: This automatically sets the minor flag in the save dialog. It can be selected or deselected in the save dialog on the page itself:






marking a minor edit

Note: Note: The 'Watch this page' checkbox in the save dialog can be activated or deactivated by default under the preferences tab *Watchlist* under *Advanced options: Add pages and files I edit to my watchlist*.

• **Prompt me when entering a blank edit summary**: Displays a text message when you click *Save changes* reminding you to enter a summary description. If you do not enter a description after that, the page will save without the summary the next time you click *Save changes*.



- Warn me when I leave an edit page with unsaved changes: When you reload or leave a page with unsaved edits, a warning message is displayed. You can confirm to leave the page or stay on the page and save your changes.
- **Show edit toolbar:** Disables VisualEditor in visual editing mode. Disabling is not recommended, as this reverts the editor back to a previous version of MediaWiki editor.
- Temporarily disable the visual editor while it is in beta: You can disable visual editor while it is in Extension: VisualEditor|beta mode. We recommend you do not disable VisualEditor unless you prefer to work with a previous visual editor version.

Preview

These preview settings are only applied if you have temporarily disabled VisualEditor and the edit text area is on the same page as the page preview. In BlueSpice 3.1+ you can generally ignore these settings.

- Show preview on first edit: The preview of the article is displayed when you click on "Edit"
- **Show preview before edit box:** If this option is deactivated, the preview will be shown under the edit form
- Show previews without loading the page:



Reminder

 Default reminder period: Prefills the date field for reminders with current date + x days specified here.



- **Set reminder on page creation:** When you create a new page, a reminder for that page is automatically created based on the default reminder period you entered.
- **Do not create reminder for the following namespaces:** Excludes namespaces from the automatic reminder on page creation.


Timeline

- Warn me when I leave an edit of an entry with unsaved changes: If unchecked, any unsaved
 changes to a social entity (such as blog entry, comment, microblog or discussion topic) will be
 automatically lost if you navigate to a different page or reload the page before saving your changes.
- **Skip dialog on discussion creation:** Automatically creates a discussion page when a user adds a discussion directly ona page and the discussion page for the entry does not yet exist. If this checkbox is unchecked, the user has to create the discussion page first before the discussion topic can be posted.

Recent changes

Display options


- **Days to show in recent changes:** You can set how many results are displayed on the page *Recent changes*.
- Number of edits to show in recent changes, (,...) by default: Setting for the filter (1) on the *Recent changes* page and similar log pages. The filter can be manually changed during page visits.



Recent changes default filter setting (1)

Advanced options

• **Group changes by page in recent changes and watchlist:** This view creates a collapsible view of all the changes on a page that occured before another page was edited. All changes still count towards the number of changes that are set in the view filter for the page.



 Use non-JavaScript interface: Removes the advanced filter option to save filters and to colorhighlight changes.

Changes shown

 Hide minor edits from recent changes: Hide edits marked as minor from appearing on your Recent changes page by default.

Edit review

These settings are provided by the extension FlaggedRevs (approval feature).



FlaggedRevs is available up to BlueSpice 4.2.

- Basic interface: This setting has no effect in the BlueSpice Discovery skin.
- When to show the stable version of content pages by default.
 - Use the default settings for each page: This setting has no effect in BlueSpice (default settings cannot be set by administrators on a page level)
 - Always show the stable version (if there is one): This default setting is only applied if the FlaggedRevs feature is active in a namespace. It shows the approved (stable) version by default when navigating to that page.
 - O **Always show the latest version:** It is a useful settings for users with review permissions who can accept draft versions. It loads the latest revision of a page by default instead of the stable version.
- Show the pending changes diff when viewing the latest pending version: This setting has no effect in the *BlueSpice Discovery* skin.



Watchlist


Edit watchlist

- Edit entries on your watchlist:
 - View and remove titles on your watchlist: Links to the page Special:EditWatchlist whre you can manage your watchlist entries. The watchlist is organized by namespaces.
 - Edit raw watchlist: Links to the page Special:EditWatchlist/raw where you can remove pages by page name from a textbox. This list is also organized by namespaces.
 - Clear watchlist: Links to the page Special:EditWatchlist/clear where you can empty your watchlist with the click of a button.

Display options

- **Days to show in watchlist** (default:7): Presets the value in the selection menu Period of time to display on the page *Special:Watchlist*.
- Maximum number of changes to show in watchlist (default:250): Limits the number of changes that are displayed in your watchlist.

This example shows a default setting of 8 days and 20 changes.



Advanced options

- **Expand watchlist to show all changes, not just the most recent** (default): Determins if a changed page is displayed several times in the filtered time period or if only the latest change is listed.
- Add direct unwatch/watch markers (×/+) to watched pages with changes (JavaScript required for toggle functionality): An icon for the direct removal of the page from the watchlist is available.





- Use non-JavaScript interface: A basic view of the watchlist loads (without special filter menu and without highlighting options).
- Add pages I review to my watchlist (until BlueSpice 4.2): Automatically adds pages the user approves to the watchlist.

Changes shown

These settings configure a standard filter for the watchlist. By default, no filter is applied. Possible standard filters are:


- Hide minor edits from the watchlist
- Hide bot edits from the watchlist
- Hide my edits from the watchlist
- Hide edits by anonymous users from the watchlist
- Hide edits by logged in users from the watchlist



Watched pages

These settings determin which pages are automatically added to the watchlist by preselecting the checkbox *Watch this page* of the related dialog window. If no dialog window is available, the addition to the watchlist automatically happens in the background:

Add pages and files I edit to my watchlist (default)



- Add pages and files I move to my watchlist
- Add pages and files I delete to my watchlist
- Add pages I create and files I upload to my watchlist (default)
- Add pages where I have performed a rollback to my watchlist



Add new files I upload to my watchlist (default)

Token


• Watchlist token: The token can be used to create a public RSS feed to your watchlist. Anyone who knows this token can access the feed. The syntax for the feed URL is: https://[YourWikiDomain]/w/api.php?action=feedwatchlist&wlowner=[USERNAME]&wltoken=[TOKEN] .

Notifications

Important! Notification don't consider the edit type "Minor edit". Therefore, notifications are sent even in the case where a user makes a minor edit.

Here you can set how and when you would like to receive notifications in email and/or in the notifications area of your user profile (Web notifications). If you haven't received email notifications yet, make sure that your email adress has been verified. This information is available in the *User profile* tab, under the section *Email options*.

To view your Web notifications, go to your User profile menu and select Notifications.




The user profile image in the main toolbar and the *Notifications* menu item show the number of new notifications. Notifications can set for a variety of events, such as new assignments or reminders. You can also select to be notified about changes only in certain namespaces or categories.

To configure which notifications you want to get, click on *Preferences* in the *Settings* menu (3).

Email options

You can specify how often you receive emails: never, immediately, daily, or weekly.





If you unexpectedly don't receive emails for notifications, check under the *User profile* tab to make sure that you have already confirmed your email account.



Notify me about these events

Notifications can be displayed in the Notifications page of the wiki. This functionality is provided by the MediaWiki extension *Echo*.

New message indicator

This setting currently has no effect in BlueSpice. It is a configuration setting for the MediaWiki extension Extension:Echo|Echo (echo-show-alert).

Notifications on namespace events

Select for which namespaces you want to receive notifications.

Notifications on categories

Select for pages in which categories you want to receive notifications.

Review

- **Notify me about changes if I am the owner of a review:** Select if you want to be notified in email of any workflow changes of a review workflow if you are the owner of the review.
- Notify me about changes if I am the reviewer of a review: Select if you want to be notified in email of any workflow changes of a review workflow if you are the owner of the review.

Under the settings for *Notify me about these events*, you can set if and how you want to be notified if someone assigns a review task to you.

Extended Search

Here you can set which namespaces you want to include in your search results. This can be useful if you work in only some areas of the wiki or if you are looking for information in a few areas of your wiki only.

Semantic MediaWiki

These user preferences are provided by Semantic MediaWiki. If you would like to change these settings, you can visit the corresponding help page.



Resetting all preferences

If you click *Restore all default settings (in all sections)*, all your customizations on all tabs are reset to their default settings. Since this could affect lots of customized settings, a warning page appears before the reset.

You can use this page to reset your preferences to the site defaults. This cannot be undone.

Restore all default settings (in all sections)

restoring default settings

Use the browser's back button if you do not want to restore the default settings.

Reference:BlueSpiceBookshelf

Extension: BlueSpiceBookshelf

(3) all extensions

| Overview | | | |
|------------------------------|--|-------------|--------------|
| Description: | Enables BlueSpice to manage and export hierarchical collections of articles. | | |
| State: | stable | Dependency: | BlueSpice |
| Developer: | HalloWelt | License: | GPL-3.0-only |
| Туре: | BlueSpice | Category: | Book |
| Edition: | BlueSpice pro, BlueSpice Farm, BlueSpice Cloud | Version: | 4.1+ |
| ② View user help page | | | |



Features

Bookshelf combines wiki pages to create books and also to export those pages as a PDF document.

- Sets of different pages (chapters) can be put together individually to a book.
- The table of contents of the book is displayed in the left navigation bar.
- The chapters are displayed in a collapsible tree structure.
- The book or parts of the book can be exported to PDF.

Configuration manager

Some aspects of this extension can be configured on Special:BlueSpiceConfigManager . Here, wiki administrators can:

- prepend the article table of contents and headlines of a page with book numeration.
- supress the namespace prefix of book articles in the PDF output.
- apply the display title from the book source to a wiki page.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.38.0

BlueSpiceFoundation: 4.1

Integrates into

- BlueSpiceBookshelf
- BlueSpiceVisualEditorConnector
- ContentDroplets
- MWStakeContentProvisioner

Special pages

- Bookshelf
- BookshelfBookEditor
- BookshelfBookManager



Permissions

| Name | Description | Role |
|--|---|--------|
| bookshelf-viewspecialpage | Access the special page Special:Bookshelf | reader |
| bookshelfbookmanager- viewspecialpage | Access the special page Special: BookshelfBookManager | reader |

Configuration

| Name | Value |
|--|--|
| BookShelfDefaultCoverImage | 'resources/images/assets/coverimage/dummy. png' |
| BookShelfShowChapterNavigationPagerAfterContent | false |
| BookShelfShowChapterNavigationPagerBeforeContent | false |
| BookshelfMainLinksBookshelf | true |
| BookshelfPrependPageTOCNumbers | true |
| BookshelfSupressBookNS | true |
| BookshelfTitleDisplayText | true |

User options

| Name | Value |
|--------------------------|-----------------|
| bs-bookshelf-defaultview | 'gridviewpanel' |

API Modules

- bs-book-chapters-store
- bs-bookshelf-bookstore
- bs-bookshelf-manage
- bs-bookshelf-mass-add-page-store
- bs-bookshelf-page-collection-store
- bs-bookshelf-store

Hooks

- BSBookshelfGetBookData
- BSUEModulePDFAfterFindFiles



MediaWik

- BSUEModulePDFbeforeGetPage
- BSUEModulePDFcollectMetaData
- BSUEModulePDFgetPage
- BSUsageTrackerRegisterCollectors
- BeforePageDisplay
- BlueSpiceDiscoveryTemplateDataProviderAfterInit
- ContentHandlerDefaultModelFor
- GetPreferences
- LoadExtensionSchemaUpdates
- MWStakeCommonUIRegisterSkinSlotComponents
- OutputPageBeforeHTML
- SkinTemplateNavigation::Universal